

ADM270 Strain Gauge Transmitter / Isolator

- Suitable for SIL 1 & SIL 2 rated (EN 61508-2) safety instrumented system (SIS) loop applications, as 1oo1 architecture (HFT:0)
- Non-Smart / Non-uProcessor based, Type A instrument
- Supply voltage options:
 - 115Vac ±20%
 - 240Vac ±20%
 - 24Vdc ±10%
 - 48Vdc ±10%
- RFI Protection to EN 61000-4-3:2006/A2:2010 available ('K' option)
- Front fascia Digital Display in % or 'other' units available ('DI' option)
- AMELEC Standard 10 year warranty

Technical Specifications

Function

Provides a DC output signal proportional to a bridge type strain gauge utilised in load cells and pressure transducers.

Input

Any mV signal range (Minimum span: 4mV)

Excitation: 10Vdc at up to 30mA as std. (5V or 24Vdc options available)

Output

Any standard process current or voltage in the range of;
Current source up to 22mA max, with drive voltage 24Vdc
(Current Sink option available, 30Vdc max external drive)

Voltage source up to 20Vdc max output

Typical Output: 4-20mA (max load 1200Ω) or 0-10Vdc (min load 500Ω)

Performance

Accuracy/Linearity: <±0.1% Span

Response Time: typically <100mS (0-100% input step change)

Supply consumption: <3VA

Protection

Isolation: 1000V RMS* Input/Excitation/Output/Supply/Earth
*(500Vdc when 'K' option RFI protection is specified)

Internal Fuse

Input over range: up to typically 300%

Input Open Circuit response: Up or Downscale drive available
(O/C response requirement to be specified at time of orders)

Environmental Conditions

Storage Temperature: -40 to +70°C



Operating Ambient: -15 to +55°C

Relative Humidity: 5 – 95% RH (Non-condensing)

EMC: 2014/30/EU , EN 61326-1:2013 (controlled EM)

('K' option: EMC/EMI/RFI protection to the highest Generic Industrial Standards Test levels)

IP Rating: IP20



Mounting: Either Din Rail (TS35) **or** Surface by corner fixing holes as standard

Dimensions: 50w x 75h x 110d mm

(DI option=145d mm, K option= 182d mm)

Tel: 01908-567003 Email: sales@amelec-uk.com Visit: www.amelec-uk.com Fax: 01908-566735

AMELEC Instruments, Cochran Close, Crownhill, Milton Keynes, MK8 0AJ